

**TOUCH PADS as Primary Timing System**

**LANE MALFUNCTION - TIME ADJUSTMENT**

EVENT:	HEAT:	ADJUSTED BY:
--------	-------	--------------

LANE	PRIMARY PAD TIME (Tp)	BUTTON A	BUTTON B	BUTTON C	T <sub>B</sub> [middle button, or average if 2, or single if one]	(Δ = Tp-T <sub>B</sub> )	Adjusted Official Time for malfunction lane (Tp + Δa)
1							
2							
3							
4							
5							
6							
7							
8							
9							
10							

<b>Sum of all valid differences</b> $\Sigma\Delta$		<b>N</b> = number of lanes with valid time
<b>Average difference of valid time</b> $\Delta a = \Sigma\Delta / N$		

**LANE MALFUNCTION - TIME ADJUSTMENT**

EVENT:	HEAT:	ADJUSTED BY:
--------	-------	--------------

LANE	PRIMARY PAD TIME (Tp)	BUTTON A	BUTTON B	BUTTON C	T <sub>B</sub> [middle button, or average if 2, or single if one]	(Δ = Tp-T <sub>B</sub> )	Adjusted Official Time for malfunction lane (Tp + Δa)
1							
2							
3							
4							
5							
6							
7							
8							
9							
10							

<b>Sum of all valid differences</b> $\Sigma\Delta$		<b>N</b> = number of lanes with valid time
<b>Average difference of valid time</b> $\Delta a = \Sigma\Delta / N$		